

## LED Panel/ 2x4/ 50W /100-277V/ 5000K



Product description: LED Panel 2x4, 50W 5000K 0-10V Dimming

Model Name: KK-PS-24EW-50-LARZ

Order SKU: 500817D

## **♦** Features

- High efficiency and energy saving
- No UV, noise, or flickering;
- High shock and vibration resistance

- Eco-friendly, Mercury-free;
- wide lighting beam angle
- Embed/Suspension/ceiling-mount









## **♦** Specifications

| Rated Voltage (V)          | 110-277V           |
|----------------------------|--------------------|
| Rated Wattage (W)          | 50W                |
|                            |                    |
| Frequency ( Hz)            | 50/60 Hz           |
| Rated Input Current (mA)   | 750mA Max          |
| Power Factor               | >0.9               |
| Luminous Flux (LM)         | 5,816.28LM         |
| Color Temperature          | Day Light 5000K    |
| Color Rendering Index (Ra) | >80                |
| Beam Angle                 | 110D               |
| Lamp Efficacy (LM/W)       | 111.13LM/W         |
| Rated Lamp Lifetime (h)    | 50,000             |
| Dimming                    | 0-10V Dimming      |
| Dimension (mm)             | 604*1214*9         |
| IP Rating                  | 20                 |
| Operating Temperature      | -20 to 45 degC     |
| Driver                     | External           |
| Certificate                | UL, CUL, DLC, Rohs |







Maximum Candeta = 1688.13 Located At Horizontal Angle = 0, Vertical Angle = 0 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) # 2 - Vertical Plane Inrough Horizontal Angles (WU - 270)