

Technical Data Sheet

ORBIT[®]-REFLECTOR

Screw-in Reflector Compact Fluorescent Lamps



Technical/Electrical Data & Physical Characteristics

Item Number	Description	Wattage	Voltage	Life	Base	CRI	Light Output	Colour Temperature	Diameter	M.O.L.	Case Qty.	Energy Star
G52040-003	SL13/0/BR30/ES/841 120V	13W	120V	8,000 hrs	E26	82	600 lm	4100K	93mm	139mm	10/20	
G52060-003	SL13/0/BR30/ES/850 120V	13W	120V	8,000 hrs	E26	82	600 lm	5000K	93mm	139mm	10/20	
G52070-003	SL16/0/BR30/ES/827 120V	16W	120V	8,000 hrs	E26	82	750 lm	2700K	93mm	139mm	10	
G52072-003	SL16/0/BR30/ES/830 120V	16W	120V	8,000 hrs	E26	82	750 lm	3000K	93mm	139mm	10	
G52074-003	SL16/0/BR30/ES/835 120V	16W	120V	8,000 hrs	E26	82	750 lm	3500K	93mm	139mm	10	
G52076-003	SL16/0/BR30/ES/841 120V	16W	120V	8,000 hrs	E26	82	750 lm	4100K	93mm	139mm	10	
G52078-003	SL16/0/BR30/ES/850 120V	16W	120V	8,000 hrs	E26	82	750 lm	5000K	93mm	139mm	10	
G52300-003	SL23/0/BR40/ES/827 120V	23W	120V	8,000 hrs	E26	82	1300 lm	2700K	120mm	159mm	10	
G52320-003	SL23/0/BR40/ES/835 120V	23W	120V	8,000 hrs	E26	82	1200 lm	3500K	120mm	159mm	10	
G52340-003	SL23/0/BR40/ES/841 120V	23W	120V	8,000 hrs	E26	82	1200 lm	4100K	120mm	159mm	10	
G52360-003	SL23/0/BR40/ES/850 120V	23W	120V	8,000 hrs	E26	82	1200 lm	5000K	120mm	159mm	10	



Symban Lighting Corp.
 99 First Gulf Blvd. Brampton, ON
 T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

Technical Data Sheet

ORBIT[®]-REFLECTOR

Screw-in Reflector Compact Fluorescent Lamps



Technical/Electrical Data & Physical Characteristics

Item Number	Description	Wattage	Voltage	Life	Base	CRI	Light Output	Colour Temperature	Diameter	M.O.L.	Case Qty.	Energy Star
G51900-003	SL9/O/PAR20/ES/827 120V	9W	120V	8,000 hrs	E26	82	320 lm	2700K	63mm	95mm	15/60	
G51910-003	SL9/O/PAR20/ES/830 120V	9W	120V	8,000 hrs	E26	82	320 lm	3000K	63mm	95mm	15/60	
G51920-003	SL9/O/PAR20/ES/835 120V	9W	120V	8,000 hrs	E26	82	320 lm	3500K	63mm	95mm	15/60	
G51930-003	SL9/O/PAR20/ES/841 120V	9W	120V	8,000 hrs	E26	82	320 lm	4100K	63mm	95mm	15/60	
G51940-003	SL9/O/PAR20/ES/850 120V	9W	120V	8,000 hrs	E26	82	320 lm	5000K	63mm	95mm	15/60	
G52100-003	SL15/O/PAR30LN/ES/827 120V	15W	120V	8,000 hrs	E26	82	700 lm	2700K	94mm	131mm	15	
G52110-003	SL15/O/PAR30LN/ES/830 120V	15W	120V	8,000 hrs	E26	82	700 lm	3000K	94mm	131mm	15	
G52120-003	SL15/O/PAR30LN/ES/835 120V	15W	120V	8,000 hrs	E26	82	700 lm	3500K	94mm	131mm	15	
G52140-003	SL15/O/PAR30LN/ES/841 120V	15W	120V	8,000 hrs	E26	82	700 lm	4100K	94mm	131mm	15	
G52160-003	SL15/O/PAR30LN/ES/850 120V	15W	120V	8,000 hrs	E26	82	680 lm	5000K	94mm	131mm	15	
G52200-003	SL23/O/PAR38/ES/827 120V	23W	120V	8,000 hrs	E26	82	1200 lm	2700K	123mm	137mm	15	
G52210-003	SL23/O/PAR38/ES/830 120V	23W	120V	8,000 hrs	E26	82	1280 lm	3000K	123mm	137mm	15	
G52220-003	SL23/O/PAR38/ES/835 120V	23W	120V	8,000 hrs	E26	82	1200 lm	3500K	123mm	137mm	15	
G52240-003	SL23/O/PAR38/ES/841 120V	23W	120V	8,000 hrs	E26	82	1200 lm	4100K	123mm	137mm	15	
G52260-003	SL23/O/PAR38/ES/850 120V	23W	120V	8,000 hrs	E26	82	1280 lm	5000K	123mm	137mm	15	



Symban Lighting Corp.
 99 First Gulf Blvd. Brampton, ON
 T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

www.symbanlighting.com