

Date:	Project Name:
Туре:	Part Number:









SABRE SERIES **LED LINEAR STRIP MS**



DESCRIPTION

Reno Lighting's Sabre Series is the LED Commercial Strip fixture is designed with a polycarbonate diffuser that provides impact resistance and even, low glare light. Combine this with powerful, high output LED chips, these fixtures meet today's stringent efficacy standards and bring your projects maximum energy savings.

FEATURES

- DLC Premium for the Stairwell and Passageway Luminaires
- 0-10V dimming control compatible
- Surface or Suspension Mounting options
- Operating temperature: -22°F to +122°F (-30°C to +50°C)
- Dual Voltage 120-347V
- Easy and Safe Installation
- Integrated microwave sensor
- Frosted Polycarbonate Lens
- Suitable for Damp location
- Rated Lifetime L70(hrs): >100,000
- Includes Coverplate and V-Hangers
- Multi CCT & Wattage
- 7 year warranty

APPLICATIONS



Parking Garage



Stairwell



Warehouse



















*THE MAXIMUM HEIGHT THIS FIXTURE CAN BE MOUNTED FOR OPTIMAL SENSOR FUNCTION IS 16-17FT. IF MOUNTED ABOVE THIS HEIGHT MOTION WILL NOT BE DETECTED AS

PRECISELY*







Date:	Project Name:
Туре:	Part Number:

SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	LUMENS	EFFICACY	CRI		
R33026	RENO-LSN2-22W-DV-MCCT-MS	22W	120-347V	3500K	3527 lm	160.3 lm/W	>80		
				4000K	3740 lm	170 lm/W			
				5000K	3542 lm	161 lm/W			
		22W			3593 lm	163.3 lm/W	>80		
		28W		0=0016	4544 lm	162.3 lm/W			
		36W		3500K	5807 lm	161.3 lm/W			
		44W			7053 lm	160.3 lm/W			
		22W			3806 lm	173 lm/W	>80		
B00000	DENIG LONG DIVINION AGOSTIAS	28W	120-347V	4000K	4816 lm	172 lm/W			
R33020	RENO-LSN4-DV-MW-MCCT-MS	36W			6156 lm	171 lm/W			
		44W			7480 lm	170 lm/W			
		22W				3608 lm	164 lm/W		
		28W			4564 lm	163 lm/W	>80		
		36W		5000K	5832 lm	162 lm/W			
		44W			7084 lm	161 lm/W			
		48W	3				7843 lm	163.4 lm/W	
		68W		3500K	11,043 lm	162.4 lm/W	>80		
R33021		90W			14,526 lm	161.4 lm/W			
		48W		7V 4000K	8304 lm	173 lm/W	>80		
	RENO-LSN8-DV-MW-MCCT-MS	68W	120-347V 4000K 5000K		11,696 lm	172 lm/W			
		90W			15,390 lm	171 lm/W			
		48W		5000K	7872 lm	164 lm/W			
		68W			11,084 lm	163 lm/W			
		90W			14,580 lm	162 lm/W			





Date:	Project Name:
Туре:	Part Number:

DLC CHART

OPPER!		APPLICATION	DLC		
ORDER#	ORDER# MODEL#	APPLICATION	STANDARD	PREMIUM	
D2202/	RENO-LSN2-22W-DV-MCCT-MS	Direct Linear Ambient Luminaires	S-SYN41L		
R33026		Stairwell and Passageway Luminaires		S-DRA2TN	
		Direct Linear Ambient Luminaires	S-XJ5NO7		
R33020 RENO-LSN4-DV-MW-MCCT-MS	Low-Bay Luminaires for Commercial and Industrial Buildings	S-CEJ1VP			
		Stairwell and Passageway Luminaires		S-SHT7R4	
		Direct Linear Ambient Luminaires	S-F8KWGX		
R33021 RENO-LSN8-DV-MW-MCCT-M	RENO-LSN8-DV-MW-MCCT-MS	High-Bay Luminaires for Commercial and Industrial Buildings	S-BD9243		
		Stairwell and Passageway Luminaires		S-5H2VSL	

ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R39501	L-BRACKET	L-Bracket for 90° Installation
R39502	I-BRACKET	I-Bracket for straight continuous Installation
R39503	RENO-LSN4-WG	LED Linear Strip Wire Guard for 4ft
R39504	RENO-LSN8-WG	LED Linear Strip Wire Guard for 8ft
R83004	RENO-EM-C08	Emergency LED Driver
R39204	RENO-RP	LED suspension kit



L-BRACKET



RENO-LSN4-WG



RENO-EM-C08



I-BRACKET



RENO-LSN8-WG



RENO-RP











Date:	Project Name:
Туре:	Part Number:

SENSOR OPTIONS

ORDER#	MODEL#	DESCRIPTION
R74002	RENO-SENSOR-PIR-H-EX	For external mounting when installed above 13FT



RENO-SENSOR-PIR-H-EX

REMOTE OPTIONS

ORDER#	MODEL#	DESCRIPTION
R73002	RENO-REMOTE-H	Controller for Bi-Level Sensor (with screen)
R73005	RENO-REMOTE-H-ECO	Remote Control for ECO LINEAR HIGHBAY/FULL CUTOFF WALLPACK/ LINEAR STRIP/VP FIXTURE (without screen)







RENO-REMOTE-H-ECO





Date:	Project Name:
Туре:	Part Number:

DIMENSIONS

