


Date:	Project Name:
Type:	Part Number:



# MAKO SERIES

## LED VAPOR TIGHT STRIP




### DESCRIPTION

Reno Lighting's ECO Vapor Tight is housed in polycarbonate silicon perimeter gasket with brackets for mounting. Engineered for powerful lighting. The Reno linear vapor tight has an IP66 protection grade and is DLC and UL certified, making it a great lighting solution for your industrial application.

### FEATURES

- DLC Standard
- 0-10V dimming control compatible
- Surface & Suspended Mounting options via supplied clamps inside the fixture body
- Operating temperature: -22°F to +122°F (-30°C to +50°C)
- Protection Grade IP66
- One-piece polycarbonate housing body and frosted polycarbonate lens
- Suitable for Wet location
- CRI >80
- Rated Lifetime L70(hrs): >70,000
- 5 year warranty

### APPLICATIONS

-  Low Bay Application
-  Parking Garage
-  Stairwell



Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	HOURS RATING	DIMMABLE	LUMENS	CCT (K)
R33118	RENO-LVP2-DV-MW-MCCT-ECO	20/25/35W	120-347V	70,000	0-10V	2680/3903/ 4137 lm	35/40/50K
R33116	RENO-LVP4-DV-MW-MCCT-R1-ECO	25/35/45W	120-347V	70,000	0-10V	2440/4672/ 5120 lm	35/40/50K
R33117	RENO-LVP4-DV-MW-MCCT-R2-ECO	50/60/66W	120-347V	70,000	0-10V	8100/10,800/ 13,550 lm	35/40/50K

## ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R83004	RENO-EM-C08	Emergency LED Driver

## SENSOR OPTIONS

ORDER#	MODEL#	DESCRIPTION
R74002	RENO-SENSOR-PIR-H-EX	For external mounting when installed above 13FT


## DIMENSIONS

2FT



78.7mm  
(3.1")

91.4mm  
(3.6")




599.4mm  
(23.6")

4FT



78.7mm  
(3.1")

91.4mm  
(3.6")



1201.4mm  
(47.3")

