

Date:	Type:
Project Name:	Part Number:

BALLAST-COMPATIBLE LED T8 TUBE (TYPE A)4FT (HIGH EFFICIENCY)



APPLICATIONS

- Office Lighting
- Commercial Applications
- Retail Lighting
- Residential

FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- Operating Temperature: -20°C to 45°C
- 50,000⁺ hours lifespan (L70)
- 5 Year Warranty

SPECIFICATION

ORDER #	MODEL #	WATTS	BASE	VOLTAGE(V)	HOUR RATING	BEAM ANGLE	INITIAL LUMENS	CCT(K)
R41020	WLL-LEDT8BC13/840/HE(4FT)	13W	G13	BF	50,000	320°	2200	4000K
R41021	WLL-LEDT8BC13/850/HE(4FT)	13W	G13	BF	50,000	320°	2200	5000K
R41024	WLL-LEDT8BC9/840/HE(4FT)	9W	G13	BF	50,000	320°	1800	4000K
R41025	WLL-LEDT8BC9/850/HE(4FT)	9W	G13	BF	50,000	320°	1800	5000K
R41023	WLL-LEDT8BC10/850/HE(4FT)	10W	G13	BF	50,000	320°	1800	5000K

DIMENSIONS

▪ 4FT

