

Date:	Type:
Project Name:	Part Number:

OPS SERIES

LED SECURITY WALL PACK



Photocell cap included

APPLICATIONS

- Commercial Building
- Exterior Parking
- School & Hospital

FEATURES

- DLC Listed
- Dual Voltage 120-347V
- High and stable lumen output
- -40°F to 104°F (-40°C to 40°C) operating temperature
- Elegant and Efficient design
- Integrated type photocell
- 50,000 hours lifespan
- 5-year Warranty
- Custom colours available
- Selectable Wattage & CCT
- IP66 Rated

SPECIFICATION

ORDER #	MODEL#	WATTS	VOLTS	BEAM ANGLE	INITIAL LUMENS	HOUR RATING	CCT
R51014	RENO-WP-25W-MW-DV-MCCT-SEN	16/20/25W	120-347V	90°	110 lpm	50,000	3500K/4000/5000K

Date:

Type:

Project Name:

Part Number:

LUMINOUS EMITTANCE

Illuminance at a Distance			
	Center Beam fc	Beam Width	
1.7ft	277 fc	3.4 ft	3.2 ft
3.3ft	73.6 fc	6.6 ft	6.2 ft
5.0ft	32.1 fc	10.0 ft	9.4 ft
6.7ft	17.8 fc	13.4 ft	12.6 ft
8.3ft	11.6 fc	16.6 ft	15.6 ft
10.0ft	8.01 fc	20.0 ft	18.8 ft

■ Vert. Spread: 90.0°
■ Horiz. Spread: 86.3°

DIMENSION

