

LED Wall Pack Light Instruction

Application:

Available in industrial lighting, landscape lighting, courtyard, building, hotel, building exterior, etc.

Caution:


- 1.Can not use the electric generator to test the LED light.
- 2.Please abide by related country, regional and local law and regulations when install this fixture.
- 3.Please don't install the fixture when raining to lower the risk of electric shock and avoid the failure.

Note:


- 1. To avoid possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
- 2. Please wear gloves to avoid injury before installation.
- 3. If any smoke or spark of the wire happened, please turn off the power immediately and notify relevant personnel.

Installation I:


1. Turn off the powe



3. Remove the 1/2 end cap



2. Loosen the 4 screws




4. Peel off the yellow sticker and paste it on the round area of the bottom plate






www.votatec.ca

5. Fix the bottom plate on the round plate




7. Fix the fixture by 4 screws




Installation II:


1. Turn off the power




3. Paste the black sponge pad on the bottom plate




6. Make wiring connection and make sure the good protection




8. Make sure good wiring and screws fastening, then turn on the power



2. Loosen the 4 screws




4. Screw the bottom plate on the wall






www.votatec.ca


5. Remove one of the 1/2 end cap and get through wire




7. Return on the fixture to the bottom plate and tighten it with screws




6. Make wiring connection and make sure the good protection



8. Turn on the power after make sure good wiring and insulation



Note: if the light is designed with CCT adjustable function, After the product base is fixture, choose the requested CCT by dip switching.



Standard wire:

L/live wire:Black\Brown;
N/null wire:White\Blue;
Ground wire:Green\Yellow-green.

DIM+ DIM- As for the wire color of DIM+ and DIM-, pls check the light label.

Warning/Avertissement:

MIN 90°C SUPPLY CONDUCTORS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

LES FILS D'ALIMENTATION 90 °C MIN

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS.